

Caracteristici						
Tip	Culoare	Comp. Oxidică	Temp. Max de utilizare	Domeniul de utilizare	sub 1 kg lei/kg	peste 1 kg lei/kg
PIGMENTI FERRO						
CK 11709	Havana	Zr PrV Fe Si	1260	V/S	53	44
CK 11020	Piersica	ZnFeSi	1260	V/S	72	60
CK 14002	Verde Crom	CrAl	1260	V/S/E	84	70
CK 12021	Bordo	SnCrCa	1200	V/S	104	87
CK 11508	Maro	FeCrZnAl	1260	V/S	40	33
CK 12032	Pinc	SnCrCaSi	1260	V/S/E	130	108
CK 10403	Galben lămâie	ZrPrSi	1260	V/S/E	128	107
CK 10025	Galben napoli	Pb Sb	1050	V/S	94	79
CK 14028	Albastru turcoaz	CrCoZn	1250	V/S/E	130	108
CK 13 074	Negru	FeCrNiMn	1260	V/S/E	104	87
CK 13100	Negru	FeCrNiMn	1260	V/S/E	74	61
CK 15090	Turcoaz	ZrVSi	1260	V/S/E	68	57
CK 270542	Roșu	ZrCdSi	1260	V/S/E	159	133
CK 230508	Portocaliu	ZrCdSi	1260	V/S/E	148	123
FERRO InstantColor						
210-950	Verde oliv	Cr Al	1400	V/S	115	96
210 946	Verde brad	ZrSiV	1300	V/S	365	304
220,942	Albastru turcoaz	Zr Si V	1350	V/S	98	82
220-944	albastru mediu	Co Al	1450	V/S	344	287
220,946	Albastru cobalt	Co Si	1450	V/S/E	301	273
230,942	Orange intensiv	Zr-Si-Cd-S-Se	1350	V/S/E	272	227
230,944	Havana okker	Zr V	1400	V/S/E	130	108
230,955	Galben	Zr V	1400	V/S/E	146	122
230,967	Melba	Zr V-In	1400	V/S/E	280	234
240-944	Negru	Ni-Nn-Fe-Cr	1300	V/S	204	170
250,960	Gri albastrui	Zr-Si-Co-Ni	1300	V/S	216	180
250-946	Gri albastrui	Sn-Sb	1300	V/S	270	225
250-942	Gri neutru	Sn-Sb-V	1300	V/S	252	210
260,952	Maro	Zn/Cr/Fe	1300	V/S	103	86
260-954	Maro mediu	Spinell	1300	V/S	124	103
270 944	Roșu intensiv	Zr-Si-CdS-Se -zăr	1250	V/S	264	220
270-548	Roșu viu	Zr-Si-CdS-Se -zăr	1250	V/S	352	305
270-966	Castaniu închis	Ca Sn Si Cr	1250	V/S	182	152
280-942	Violet	SnCr	1250	V/S	303	252
259-954	Gri		1250	V/S	137	114
270,552	Rosu		1250	V/S	179	149
FK 6904	Rosu pompier		1250	V/S	252	210
Legenda: V- Vitrus, S- Sanitare, E- Email			Actualizat la 24.03.2017			